

| MODEL | METAL | PTFE |
|------------|---------------|----------------|
| W/O LEVER | SV-B27 | SVP-B27 |
| WITH LEVER | SV-B29 | SVP-B29 |

SV-B27/SV-B29 optional Pressure: 10.5~20 kgf/cm²

The Disc can be replaced with **PTFE** for good effect of anti-leakage. (Model: SVP-B27, SVP-B29)

When placing order, please indicate **Working Pressure**.



| | |
|----------------------------|---|
| Working Fluid | SV-B27/SV-B29/SVP-B29 Non-Corrosive Gas, Air, Steam. SVP-B27 (W/O Lever) Non-Corrosive Gas, Non-Corrosive Liquid, Air, Steam, Water, Oil. |
| Working Temperature | -45°C ~ 185°C |
| Working Pressure | SV-B27 / SV-B29 0.3 ~2 kgf/cm ² , 2.1 ~ 10 kgf/cm ² , 11 ~ 20 kgf/cm ² SVP-B27 / SVP-B29 (PTFE) 7 ~ 10 kgf/cm ² |
| Connection | BSPT (BS21), NPT (ANSI B2.1) |

This type of safety valve is characterized by regulating of pressure in valve rising and blowing-out when actuated and is the smallest and lightest valve, and also can be used in non-corrosive gases (air, oxygen, nitrogen, etc.) steam and liquids, such as water and oil. The sizes shown in the chart are subject to change without notice.